

# CertainTeed



## Flexible Corner Trim

### Product Data and Submittal

#### Product Description

CertainTeed LEVELLINE® Flexible Corner Trim is a drywall corner that comes in a 2.75" (69.9 mm) x 100' (30.5 m) roll and flexes to any inside or outside corner angle. It is perfect for cathedral ceilings, inside and outside corners, and bay windows.

#### LEVELLINE® Flexible Corner Trim

#### Construction

LEVELLINE Corner Trim has a high strength, tapered copolymer core. It is faced with a tight fibered formulated paperboard and is backed with a joint tape paper for uniform surface bonding. The memory-free hinge makes it easy to adjust.

#### Durability

The uniform structural bonding with corner prevents cracks and call-backs. Corners will not dent or separate from the wall, withstanding any significant shifting due to settling, lumber drying, temperature and humidity variations.

#### Product Data

**Packaging:** 100' (30.5 m) rolled lengths 12 rolls per carton

**Dimensions:** Copolymer center thickness approximately: .034" (1 mm)  
Copolymer edge thickness approximately: .02" (0.5 mm)  
Total flange width: 1.38" (35 mm)  
Copolymer flange width: .88" (22 mm)  
Paperboard edge flap: .5" (13 mm)

**Storage:** Protect from excess moisture. Do not stack material more than 2 pallets high. Rotate stock.

**Technical References:** For additional information on the application and finishing of CertainTeed Brand Finishing Products please consult:

- ASTM C1047: Standard Specification for Accessories for Gypsum Board and Gypsum Veneer Base (accessories used in conjunction with assemblies of gypsum wallboard and gypsum veneer base to protect edges and corners and to provide architectural features).

#### Working with the Product

#### Site conditions

The room temperature and wallboard should be maintained at 55°F (13°C) for 48 hours prior to application and continuously thereafter until compound is completely dry. Gypsum wallboard should be dry for at least 48 hours before the application of joint compounds. Continuous ventilation must be provided to ensure proper drying.

#### Application

Embed bead into compound and remove excess compound by wiping with a drywall knife. Allow compound to dry and then coat the outside tabs to finish corner. If necessary, sand once compound is dry and recoat edges until desired finish is achieved.

#### SDS

Safety Data Sheets are available on our web site, [www.CertainTeed.com](http://www.CertainTeed.com).

For further information, refer to Safety Data Sheet or consult manufacturer by calling 1-800-233-8990.

**KEEP OUT OF REACH OF CHILDREN.**

Continued on back

Job Name

Contractor

Date

Products Specified:

Submittal Approvals  
(Stamps or Signatures)

**CertainTeed**  
SAINT-GOBAIN

## Warranty

Since methods and conditions of application such as temperature, humidity and over thinning are beyond our control, CertainTeed Gypsum Inc. (CertainTeed) will not be responsible for the failure of this Product when the Product is not used according to directions and specifications and accepted standards of procedure inherent in drywall application; or when reasonable allowance is not made by the user for adverse weather and job

conditions. However, if this Product proves to be defective, maximum liability shall be limited to replacement of the material only or refund of the purchase price. This shall be the full limit whatsoever of CertainTeed's liability. All claims shall be submitted in writing to CertainTeed within thirty days from the date of discovery. State/Provincial or Federal laws may provide rights in addition to this warranty that cannot be modified or excluded.



**CertainTeed**  
SAINT-GOBAIN

### CertainTeed Corporation

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM

20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 [certainteed.com](http://certainteed.com)