

STOCK#	NAME	PCS/BOX
#9250	1 Hour Fire Bead™ 10'	12
#9260	2 Hour Fire Bead™ 10'	12

Description: Trim-Tex® Fire Bead™ is a fire rated wall mount deflection bead that provides 1- and 2-hour fire-ratings for both dynamic and static joints according to UL-2079 5th edition (for both standard walls and shaft walls) and is sound tested according to ASTM E90.

Advantages: Made from rust proof, dent resistant PVC to reduce jobsite and handling damage. Does not contain cellulose, a potential food source for mold. Intumescent tape expands when exposed to flame for increased fire protection.

Limitations: Product is designed for interior use.

Surface Characteristics: Trim-Tex® products are made from PVC. PVC does not support combustion and is self-extinguishing when the source of flame or heat is removed.

Installation: Ensure wall sections are built to UL 2079 specifications. Detailed installation instructions can be found at www.Trim-Tex.com.

Accessories: Safety Products distributed by Trim-Tex®.


ASTM & Code Standards:

- ASTM E 1966: Standard Test Method of Fire Tests of Firestop Systems – UL 2079 5th Edition Tests for Fire Resistance of Building Joints.
- ASTM E-119 Standard Test Methods for Fire Tests of Building Construction and Material.
- Sound Tested in accordance with ASTM E90-09.
- Air leakage tests conducted for compliance with Section 713.6 of IBC and CBC.
- Intumescent Firestopping tested per ASTM E 84 UL723, Flame Spread 5, Smoke Index 5.
- UL listings/approvals – HW-D-0624; HW-D-0625; HW-D-0554; HW-D-0550; BW-S-0024; WW-D-0104.

Job Name _____

Contractor _____

Date _____



Approvals (Signatures or Stamps)